

7TH GENERATION N-SERIES BUS
EXPERIENCE
more



ISUZU

N-SERIES BUS

	NMR85H	NQR81M COWL	NQR81M ZURI
Models	NMR85U-HH5AY	NQR81U-MN5VAY(Cowl)	NQR81U-MN5VBY(Yagura)
Axle Layout	4x2	4x2	4x2
Rear Tyre	Dual	Dual	Dual
Seats	25	33	29
ENGINE			
Model	4JJ1 - TC	4HL1-TCS	4HL1-TCS
Type	Diesel 4 Cylinder, Common Rail Turbocharged with Intercooler	Diesel 4 Cylinder, Common Rail Turbocharged with Intercooler	Diesel 4 Cylinder, Common Rail Turbocharged with Intercooler
Displacement (cc)	3000	4778	4778
Max Output, hp (kW) @ rpm	124 (91) @ 2,600	150 (114) @ 2,600	150 (114) @ 2,600
Max Torque, Nm (Kgm) @ rpm	354 (36.12) @ 1,500-2,600	402 (41) @ 1,500-2,600	402 (41) @ 1,500-2,600
Pre-air Cleaner & High Air Intake Pipe	Standard	Standard	Standard
Fuel Water Sedimentors	Standard	Standard	Standard
Heavy Duty Radiator	Standard	Standard	Standard
Emission	Euro IV	Euro IV	Euro IV
CLUTCH			
Type	Single Dry Plate	Single Dry Plate	Single Dry Plate
Diameter (mm/inch)	300/12"	325/13"	325/13"
Operation	Hydraulic Control	Hydraulic Control	Hydraulic Control
TRANSMISSION			
Make / Model	MYT-5T	MYT-6S	MYT-6S
	Manual, 5 Speed/1 Reverse	Manual, 6 Speed/1 Reverse	Manual, 6 Speed/1 Reverse
SUSPENSION			
Front & Rear	Semi-Elliptical, Alloy Steel Leaf Springs with Double Acting Telescopic Shock Absorbers		
BRAKES			
System	Vacuum Assisted, Hydraulic Dual Circuit	Hydraulic Brake Booster, Hydraulic Dual Circuit	Hydraulic Brake Booster, Hydraulic Dual Circuit
Front & Rear	Drum	Drum	Drum
Park Brake	Mechanical, at Rear of Transmission	Mechanical, at Rear of Transmission	Mechanical, at Rear of Transmission
Auxiliary	Exhaust Brake	Exhaust Brake	Exhaust Brake
Speed Limiter	80km/h	80km/h	80km/h
STEERING			
Operation	Power	Power	Power
Tilt	Standard	Standard	Standard
INTERIOR			
Seat Belt	3 Point x 2 for Driver & Assistant Seat, 2 Point x 1 for Centre Seat	3 Point x 2 for Driver & Assistant Seat, 2 Point x 1 for Centre Seat	3 Point x 2 for Driver & Assistant Seat, 2 Point x 1 for Centre Seat
Radio with USB,BT,AM & FM Receiver	Standard	Standard	Standard
WHEELS & TYRES			
Tubeless Tyre	Standard	Standard	Standard
Tyre Size	7.00R16	9.5R17.5	9.5R17.5
Rim Size	16x5.5	17.5x6	17.5x6
FUEL TANK			
Capacity (Litres)	100	100	100
Fuel Tank Lock	Standard	Standard	Standard
FRONT AXLE			
Front Axle Capacity (kg)	2900	3300	3300
REAR AXLE			
Rear Axle Capacity	5000	6600	6600
Final Drive Ratio (:1)	5.125	5.125/5.571	5.125/5.571
ELECTRICAL SYSTEM			
Battery	12V-NS70 X2	12V-NS70 X2	12V-NS70 X2
Alternator	24V - 90A	24V - 80A	24V - 80A
DIMENSIONS (mm)			
OL – Overall Length	6030	7815	7815
OW – Overall Width	1815	2040	2040
OH – Overall Height	2160	2275	2275
WB – Wheelbase	3345	4475	4475
FOH – Front Overhang	1110	1110	1110
ROH – Rear Overhang	1575	2230	2230
WEIGHT (kg)			
Gross Vehicle Weight	5500	8500	8500
Cab Chassis Mass	2090	2845	2845
FLEET MANAGEMENT SYSTEM			
FMS SYSTEM	Equipped	Equipped	Equipped

MORE SUPPORT

Receiving your new Isuzu N-Series is just the beginning of your relationship with us. Our comprehensive aftersales solutions cover servicing, locally available parts, driver certification and in the unlikely event that you should need our help, roadside assistance, available all year round.